



Product Service

# CERTIFICATE

No. U6 18 05 03171 006

**Holder of Certificate:** Shanghai Euchips Industrial Co.,Ltd4F, Building 6, No.888 Shuangbai Rd  
201108 Shanghai  
PEOPLE'S REPUBLIC OF CHINA**Production Facility(ies):** 03171**Certification Mark:****Product:** Electronic controlgear for LED modules  
LED Driver**Model(s):** EUP series  
(See attachment for details of model description)**Parameters:**  
Rated voltage: 220-240V~  
Rated frequency: 50/60Hz  
Output voltage: see attachment  
Output current: see attachment  
Protection Class: Class I  
Degree of protection: IP20  
ta: -20 - 50°C;  
tc: 90°C;  
Install Classification: Independent**Tested according to:** EN 61347-1:2015  
EN 61347-2-13:2014/A1:2017  
EN 62384:2006/A1:2009

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. The certification mark must not be altered in any way. See also notes overleaf.

**Test report no.:** 704021705947-00**Date,** 2018-05-17  
(Na Zhang)

Page 1 of 3



**CERTIFICATE**  
**No. U6 18 05 03171 006**



Product Service

Model name	Input voltage (VAC) / frequency (Hz)	Output voltage(VDC)	Irated (A)	Prated (W)
EUP200A-1H24V-1	220-240 / 50/60	24	max. 8.3	max. 200
EUP200D-1H24V-0	220-240 / 50/60	24	max. 8.3	max. 200
EUP200AD-1H24V-0	220-240 / 50/60	24	max. 8.3	max. 200
EUP200T-1H24V-0	220-240 / 50/60	24	max. 8.3	max. 200
EUP200-1H24V-0MTL	220-240 / 50/60	24	max. 8.3	max. 200
EUP200A-1H12V-1	220-240 / 50/60	12	max. 16.6	max. 200
EUP200D-1H12V-0	220-240 / 50/60	12	max. 16.6	max. 200
EUP200AD-1H12V-0	220-240 / 50/60	12	max. 16.6	max. 200
EUP200-1H12V-0MTL	220-240 / 50/60	12	max. 16.6	max. 200
EUP200T-1H12V-0	220-240 / 50/60	12	max. 16.6	max. 200
EUP150A-1H24V-1	220-240 / 50/60	24	max. 6.25	max. 150
EUP150D-1H24V-0	220-240 / 50/60	24	max. 6.25	max. 150
EUP150AD-1H24V-0	220-240 / 50/60	24	max. 6.25	max. 150
EUP150T-1H24V-0	220-240 / 50/60	24	max. 6.25	max. 150
EUP150-1H24V-0MTL	220-240 / 50/60	24	max. 6.25	max. 150
EUP150A-1H12V-1	220-240 / 50/60	12	max. 12.5	max. 150
EUP150D-1H12V-0	220-240 / 50/60	12	max. 12.5	max. 150
EUP150AD-1H12V-0	220-240 / 50/60	12	max. 12.5	max. 150
EUP150T-1H12V-0	220-240 / 50/60	12	max. 12.5	max. 150
EUP150-1H12V-0MTL	220-240 / 50/60	12	max. 12.5	max. 150
EUP120A-1H24V-1	220-240 / 50/60	24	max. 5	max. 120
EUP120D-1H24V-0	220-240 / 50/60	24	max. 5	max. 120
EUP120AD-1H24V-0	220-240 / 50/60	24	max. 5	max. 120
EUP120T-1H24V-0	220-240 / 50/60	24	max. 5	max. 120
EUP100-1H24V-0MTL	220-240 / 50/60	24	max. 5	max. 120

**CERTIFICATE**  
**No. U6 18 05 03171 006**



Product Service

EUP120A-1H12V-1	220-240 / 50/60	12	max. 10	max. 120
EUP120D-1H12V-0	220-240 / 50/60	12	max. 10	max. 120
EUP120AD-1H12V-0	220-240 / 50/60	12	max. 10	max. 120
EUP120T-1H12V-0	220-240 / 50/60	12	max. 10	max. 120
EUP100-1H12V-0MTL	220-240 / 50/60	12	max. 10	max. 120
EUP75A-1H24V-1	220-240 / 50/60	24	max. 3.1	max. 75
EUP75D-1H24V-0	220-240 / 50/60	24	max. 3.1	max. 75
EUP75AD-1H24V-0	220-240 / 50/60	24	max. 3.1	max. 75
EUP75T-1H24V-0	220-240 / 50/60	24	max. 3.1	max. 75
EUP70-1H24V-0MTL	220-240 / 50/60	24	max. 3.1	max. 75
EUP60-1H24V-0MTL	220-240 / 50/60	24	max. 3.1	max. 75
EUP75A-1H12V-1	220-240 / 50/60	12	max. 6.2	max. 75
EUP75D-1H12V-0	220-240 / 50/60	12	max. 6.2	max. 75
EUP75AD-1H12V-0	220-240 / 50/60	12	max. 6.2	max. 75
EUP75T-1H12V-0	220-240 / 50/60	12	max. 6.2	max. 75
EUP70-1H12V-0MTL	220-240 / 50/60	12	max. 6.2	max. 75
EUP60-1H12V-0MTL	220-240 / 50/60	12	max. 6.2	max. 75
EUP40A-1H24V-1	220-240 / 50/60	24	max. 1.7	max. 40
EUP40D-1H24V-0	220-240 / 50/60	24	max. 1.7	max. 40
EUP40AD-1H24V-0	220-240 / 50/60	24	max. 1.7	max. 40
EUP40T-1H24V-0	220-240 / 50/60	24	max. 1.7	max. 40
EUP35-1H24V-0MTL	220-240 / 50/60	24	max. 1.7	max. 40
EUP40A-1H12V-1	220-240 / 50/60	12	max. 3.3	max. 40
EUP40D-1H12V-0	220-240 / 50/60	12	max. 3.3	max. 40
EUP40AD-1H12V-0	220-240 / 50/60	12	max. 3.3	max. 40
EUP40T-1H12V-0	220-240 / 50/60	12	max. 3.3	max. 40
EUP35-1H12V-0MTL	220-240 / 50/60	12	max. 3.3	max. 40