



LED Strip

SC-2835HLS



Features

- Eco friendly.
- Long life span,standard warranty 3 years.
- Complete cut / connection accessories.
- No need of constant-current power feed.
- Low power consumption.
- Custom packing.
- Waterproof silicon sleeved IP65


Application

- Cove lighting.
- Architectural lights for canopy,corridor>window, archway.
- Backlight or edge lighting for signage.
- DIY lights for home use.
- Path and contour marking.
- Decorative lights for holiday,event,show,exhibition.




Electric-Optical Characteristics (T_J=25°C)

Order Code	Color	CCT (K)	Input Voltage (CV)	LED lm(M)	Efficiency (Lm/W)	Number of LEDs (M)	Power (W/M)	IP	CRI
SC-2835HLS-SWW-24V	Warm White	2700K	24	997lm	90	126	11	65	90
SC-2835HLS-WW-24v	Warm White	3000K	24	1017lm	92	126	11	65	90
SC-2835HLS-NW-24V	Natural White	4000K	24	1084	96	126	11	65	90






Dimension(mm/inch)




Installation



Safety Information

- The strip itself and all its components may not be mechanically stressed.
- Assembly must not damage or destroy conducting paths on the circuit board.
- Installation of LED ribbon (with power supplies) needs to be made with regard to all applicable electrical and safety standards. Only qualified personnel should be allowed to perform installations.
- Correct electrical polarity needs to be observed. Wrong polarity may destroy the strip.
- Parallel connection is highly recommended as safe electrical operation mode.
- Serial connection is not recommended. Unbalanced voltage drop can cause hazardous overload and damage the strip.
- Please ensure that the power supply is of adapters power to operate the total load.
- When mounting on metallic or otherwise conductive surfaces, there needs to be an electrical isolation points between strip and the mounting surface.
- Pay attention to standard ESD precautions when installing the strip.
- Damaged by corrosion will not be honored as a materials defect claim. It is the user's responsibility to provide suitable protection against corrosive agents such as moisture and condensation and other harmful elements.

✂ Packing information



✂ Connectors

